





PCT / SE 2004 / 001136

12-08-2004



INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport




I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.




Signed

Andrew Jones

Dated

7 July 2004

PRIORITY DOCUMENT
SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH
RULE 17.1(a) OR (b)



18 JUL 83 E823430-19 000389
P01/7700 0.00-0316748.3

The Patent Office

Cardiff Road
Newport
South Wales
NP10 8QQ

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

1. Your reference

P17479GB-NHF/SJP/mm

2. Patent application number

(The Patent Office will fill in this part)

0316748.3

3. Full name, address and postcode of the or of each applicant (underline all surnames)

AUTOLIV DEVELOPMENT AB
S-447 83 Vargarda
SWEDEN

Patents ADP number (if you know it)

32108009

If the applicant is a corporate body, give the country/state of its incorporation

SWEDEN

4. Title of the invention

IMPROVEMENTS IN OR RELATING TO A CRASH DETECTION SYSTEM

5. Name of your agent (if you have one)

Forrester Ketley & Co.

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

Forrester House
52 Bounds Green Road
London
N11 2EY

Patents ADP number (if you know it)

133001 ✓

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)

Date of filing
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

- a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an applicant, or
 - c) any named applicant is a corporate body.
- See note (d))

YES

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description 13

Claim (s) 4

Abstract 1

Drawing (s) 34

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (*Patents Form 7/77*)

Request for preliminary examination and search (*Patents Form 9/77*) ONE

Request for substantive examination (*Patents Form 10/77*)

Any other documents
(please specify)

11. I/We request the grant of a patent on the basis of this application.

Signature

S. J. Parry
Forrester Kelley & Co.

Date

16 July 2003

12. Name and daytime telephone number of person to contact in the United Kingdom

S.J. PARRY
(020) 8889 6622

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- a) *If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.*
- b) *Write your answers in capital letters using black ink or you may type them.*
- c) *If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.*
- d) *If you have answered 'Yes' Patents Form 7/77 will need to be filed.*
- e) *Once you have filled in the form you must remember to sign and date it.*
- f) *For details of the fee and ways to pay please contact the Patent Office.*

PATENTS ACT 1977

P17479GB - NHF/ns/jw

5 DESCRIPTION OF INVENTION

**"IMPROVEMENTS IN OR RELATING TO A CRASH DETECTION
SYSTEM"**

10

THE PRESENT INVENTION relates to a crash detection system and more particularly relates to a crash detection system mounted on a motor vehicle such as a motor car.

15

Many types of crash detection system have been proposed previously, and many crash detection systems are complex and/or expensive. The present invention seeks to provide an improved crash detection system.

20

According to the present invention, there is provided a crash sensor arrangement in a motor vehicle, the crash sensor arrangement including a first set of sensors comprising respective sensor on each side of the vehicle, each sensor being an accelerometer having a predetermined sensing axis, each sensor being mounted on the vehicle close to the outer skin of the vehicle and at a first longitudinal position such that the sensing axis of each sensor makes a predetermined angle to the longitudinal axis of the vehicle, the predetermined angle being between 30° and 60°, or between -30° and -60°, the sensing axes being mirror symmetrical to each other relative to the longitudinal axis of the vehicle, so that at the said first longitudinal position there are only said two

25

respective sensors, the sensing axes of the two sensors extending in different directions.

Preferably, the predetermined angle is between 40° and 50° , or -40° and -50° .

Advantageously, the predetermined angle is substantially 45° , or -45° . An advantage of this is that the angles are orthogonal providing a very high degree of sensitivity and a good response in an impact situation.

10

Conveniently, the sensing axes of the sensors are directed forwardly and outwardly of the vehicle.

Preferably, the sensing axes are directed rearwardly and outwardly of the vehicle.

15

Advantageously, the sensors are mounted on the vehicle adjacent the "B" posts of the vehicle.

Conveniently, the sensors are mounted on the vehicle adjacent the "C" posts of the vehicle.

20

Preferably, the vehicle is additionally provided with a second set of sensors comprising two further crash sensors, mounted on respective sides of the vehicle at a second longitudinal position spaced from the first longitudinal position. The spacing between the sensors of the first set of sensors and the sensors of the second set of sensors provide an enhanced sensitivity and helps ensure that signals of a high quality are generated which can be processed so that an appropriate signal is generated when an impact occurs.

25

Advantageously, each further crash sensor of the second set of sensors is a contact sensor.

5 Conveniently, each further crash sensor of the second set of sensors is an accelerometer located close to the outer skin of the vehicle, the sensing axis of the sensors of the second set of sensors being mirror symmetrical to each other relative to the longitudinal axis, but also extending in directions which differ from the directions of the axis of the sensors of the first set of sensors. An
10 arrangement of this type is provided two pairs of sensors, the first pair of sensors being located at one longitudinal position and the second pair of sensors being at a second longitudinal position spaced from the first longitudinal position. The sensing axis of each pair of sensors are mirror symmetrical about the longitudinal axis. The sensors of each pair have a
15 different sensor axis, thus providing a sophisticated and responsive sensor system.

Preferably, the accelerometer of each sensor of the second set of sensors has a sensing axis which extends substantially perpendicularly to the
20 longitudinal axis of the vehicle.

Advantageously, each sensor of the second set of sensors is mounted on the vehicle adjacent an "A" post of the vehicle, or in a door of the vehicle.

25 Conveniently, the vehicle is provided with at least one front sensor.

Preferably, the vehicle is provided with two front sensors.

In one embodiment, the or each front sensor is a contact sensor.

Alternatively, the or each front sensor is an accelerometer.

5 In one arrangement, the sensing axis of each accelerometer forming a front sensor is substantially aligned with the longitudinal axis of the vehicle.

In an alternative arrangement, the sensing axis of each accelerometer forming a front sensor is between 30° and 60° , or between -30° and -60°
10 relative to the longitudinal axis of the vehicle, the axis of the front sensors being mirror symmetric relative to the longitudinal axis.

Advantageously, a central control unit is provided to receive signals from the sensors and to control the deployment or actuation of one or more
15 safety devices within the vehicle.

Conveniently, all of the sensors are located close to the outer skin of the vehicle. An advantage of an arrangement of this type is that no central sensor is provided. The sensors of the arrangement are all located close to the outer skin
20 of the vehicle, but the combination of signals generated by the sensors is capable of providing a very reliable output.

In order that the invention may be more readily understood, and so that further features thereof may be appreciated, embodiments of the invention will
25 now be described, by way of example, with reference to the accompanying drawings in which:

FIGURE 1 is a view of a vehicle provided with a crash detection system in accordance with the invention being involved in a crash;

FIGURE 2 is a view corresponding to Figure 1 illustrating a second embodiment of the invention;

5 FIGURE 3 is a view corresponding to Figure 2 illustrating another embodiment of the invention;

FIGURE 4 is a view of a vehicle provided with a crash detection system in accordance with yet another embodiment of the invention;

10

FIGURE 5 is a view corresponding to Figure 4 illustrating another vehicle provided with another crash detection system in accordance with the invention;

15 FIGURE 6 is another view corresponding to Figure 4 illustrating yet another vehicle provided with yet another crash detection system in accordance with the invention; and

20 FIGURE 7 is a diagrammatic illustration provided for purposes of explanation.

It will be understood, from the following the description, that in none of the described embodiments is there a central accelerometer. It has been proposed, in many crash detection systems, to utilise a central accelerometer
25 which is mounted centrally of the vehicle and which serves the function of determining the overall acceleration applied to a vehicle in an impact situation. The sensor arrangement of the present invention makes it unnecessary for there to be such a central accelerometer.

Referring initially to Figure 1 of the accompanying drawings, a motor vehicle 1, provided with a sensor arrangement according to the invention is shown involved in a side impact with another vehicle 2.

5

The vehicle 1 is provided with two separate sensors 3,4, each mounted on or in the region of a "B" post of the vehicle. The sensors 3,4 are thus mounted on opposite sides of the vehicle. The sensor 3 is an accelerometer which is configured to determine the acceleration applied to the vehicle in the
10 direction of a sensing axis 5. The sensing axis 5 is inclined at an angle of 45° to a longitudinal axis 6 of the vehicle with the sensing axis 5 thus being directed generally forwardly and to one side of the vehicle.

The sensor 4 is a corresponding sensor, again with a sensing axis 7
15 which is inclined at 45° to the longitudinal axis 6 of the vehicle again with the sensing axis being directed forwardly and outwardly of the vehicle.

It is to be appreciated that in the described embodiment the sensing axis of the two sensors are mirror image symmetrical about the longitudinal axis 6
20 of the vehicle.

Here it is to be explained that the sensor in the form of an accelerometer may measure acceleration in either sense along the sensing axis. For example, if a sensor in the form of an accelerometer were positioned with the sensing
25 axis parallel to the longitudinal axis of the vehicle, the sensor would be responsive to either forward acceleration of the vehicle or rearward acceleration of the vehicle.

In this Specification, when reference is made to a sensing axis which is inclined with a positive angle relative to the longitudinal axis of the vehicle, the angle identified is an angle measured from the longitudinal axis of the vehicle in an "outboard" sense, and thus depends upon the position of the sensor. As
5 can be seen from Figure 1, the sensing axis of the two sensors described, which each are inclined at 45° of the longitudinal axis of the vehicle, are directed outwardly and forwardly relative to the vehicle. Of course, the axis is not unidirectional and can be considered to be extended inwardly and rearwardly of the vehicle.

10

It has been found that the provision of two accelerometers, with sensing axes as described, may be relied upon to provide adequate information concerning any impact in which the vehicle is involved. Should the vehicle be involved in a frontal impact, thus experiencing a substantial deceleration in
15 alignment with the longitudinal axis 6 of the vehicle, components of that deceleration will be sensed equally by the sensors 3 and 4. Should the vehicle be involved in a side impact, as shown in Figure 1, the sensor 4 would generate a very substantial signal as that sensor will be moved, as a consequence of the impact, in a direction almost in alignment with the sensing axis 7. The sensor
20 3, on the other hand, will generate a much lower signal since any movement imparted to the sensor 3 may be almost perpendicular to the sensing axis 5. Consequently the nature of the impact can be determined. A significant advantage of this type of arrangement is therefore that, by using only two sensors, an arrangement can be provided which can detect and determine both
25 front and side impacts. It is advantageous to position the two sensors close to the outer skin of the vehicle because this has been found to provide significantly improved signals in the event of a side impact than would be the case if the sensors were located more centrally.

Whilst, in the described embodiment, the sensors are inclined at 45° to a longitudinal axis 6, this is the absolute optimum position, since the sensing axis of the two sensors are orthogonal. It is believed that adequate results may be achieved if the angle of inclination is between 40° and 50° and it is also thought practicable to utilise sensors where the angle of inclination is between 30° and 60° .

Whilst, in the embodiment of Figure 1, the sensing axes 5,7 were directed generally forwardly, it is equally possible for the sensing axes to be directed rearwardly. Figure 2 illustrates an alternative embodiment of the invention in which a vehicle 11 provided with a sensor arrangement in accordance with the invention is being impacted by a second vehicle 12. The vehicle 11 is provided with a first sensor 13 provided on one side of the vehicle and a second sensor 14 provided on the opposite side of the vehicle, the sensors being mounted on the vehicle in the region of the "B" posts of the vehicle. The first sensor 13 is an accelerometer having a sensing axis 15 which is inclined, relative to the longitudinal axis 16 of the vehicle, with an angle of -45° .

Here it is to be understood that a negative angle between a sensing axis and the longitudinal axis implies that the axis is inclined forwardly and to the inboard part of the vehicle, and thus may equally be considered to be inclined rearwardly and to the outboard of the vehicle, as shown in Figure 2.

Similarly the sensor 14 is an accelerometer having a sensing axis 17 which again is inclined rearwardly and to the side of the vehicle making an angle of -45° to the longitudinal axis. Whilst the angle of -45° is optimum, as the sensing axis of the sensors are orthogonal alternative angles may be utilised.

It is to be appreciated that in an off-set frontal impact as shown in Figure 2, the sensor 13 would generate a high signal as the line of force of the impact is substantially aligned with the sensing axis 15 of the sensor 13. However, the sensor 14 may produce only a very low signal.

Figure 3 illustrates a further embodiment of the invention which is effectively a modification of the embodiment shown in Figure 2. In the embodiment of Figure 3 the vehicle 11 is provided, in addition to the first set of crash sensors constituted by the accelerometers 13,14 with a second set of sensors constituted by two further crash sensors, namely a sensor 18 provided on the first side of the vehicle and a sensor 19 mounted on the opposite side of the vehicle. The sensors 18,19 may be mounted adjacent the "A" posts of the vehicle or in the front doors of the vehicle. The crash sensors 18,19 may be contact sensors, responding to an actual contact with another vehicle or object, but in the described embodiment are accelerometers. The accelerometer 18 has a sensing axis 20 which is directed perpendicularly to the longitudinal axis 16 of the vehicle, with the sensing axis 20 being directed outwardly away from the vehicle. Similarly the sensor 19 is an accelerometer having a sensing axis 21 which again is directly outwardly away from the vehicle perpendicularly to the longitudinal axis 16.

The presence of the two additional sensors 18 and 19 will enhance the sophistication of the described arrangement, and will enable more accurate assessments to be made in certain accident situations. It has been found that if the increased cost involved in providing more than two sensors can be justified for a particular vehicle installation, then the additional sensors are most beneficial if they are also positioned close to the outer skin of the vehicle, but spaced apart. Such locations for the sensors gives more and quicker

information about an impact than if a central sensor or several sensors at the same locations are used.

Figure 4 illustrates an embodiment of the invention which is effectively a modification of the embodiment shown in Figure 1. In addition to the sensors 3,4, the vehicle is provided with two further sensors 31,32 mounted at the front of the vehicle in association with the front bumper 33. These sensors may be contact sensors, adapted to generate an output signal when the sensors actually make contact with an object, such as another vehicle, or may be accelerometers having sensing axes 34,35 which are aligned with the central axis 6 of the vehicle.

The various sensors are shown, in Figure 4, as being connected to a central processing unit 36. The processing unit 36 may be located at any convenient location and will, in response to signals from the sensors, generate appropriate triggering signals to actuate safety devices present within the vehicle such as air-bags or pretensioners.

Figure 5 illustrates a further embodiment of the invention. In this embodiment of the invention a vehicle 41 is provided with a first set of sensors constituted by two side mounted sensors 42,43 each mounted at the base of the "C" post of the vehicle, the sensors being on opposite sides of the vehicle. Each sensor is an accelerometer, with each accelerometer having a sensing axis 44, 45 which makes an angle of 45° with the longitudinal axis 6 of the vehicle. Each sensing axis is thus directed outwardly and forwardly of the vehicle. the sensing axes are mirror image symmetrical about the longitudinal axis of the vehicle. The vehicle is provided with a second set of sensors constituted by two further sensors 46,47, each mounted in the front door or adjacent one of the "A" posts of the vehicle, the sensors 46 and 47 thus being on opposite sides of

the vehicle. The sensors 46,47 may be contact sensors but are preferably accelerometers, with each accelerometer having a sensing axis 48,49 which is directed perpendicularly relative to the longitudinal axis of the vehicle in a sense outwardly away from the vehicle.

5

The vehicle is provided with two additional sensors 50,51 mounted in the region of the front bumper 52 of the vehicle. The sensors 50,51 may be contact sensors which respond when the vehicle makes contact with another object or may be accelerometers, in which case the accelerometers may preferably have sensing axes 53,54 which are substantially aligned with the longitudinal axis 6 of the vehicle. In alternative embodiments of the invention, the sensors 50,51 may be accelerometers which have sensing axis which are inclined between 30° and 60° , or between -30° and -60° relative to the longitudinal axis of the vehicle, the axis being mirror symmetric relative to the longitudinal axis of the vehicle.

15

The sensors are connected to a central control unit 55 which corresponds with the control unit 36 of the embodiment described above with reference to Figure 4. In this embodiment it is to be noted that the sensors with the inclined sensing axes are located towards the rear of the vehicle.

20

Referring now to Figure 6, a further embodiment of the invention is illustrated. In this embodiment of the invention, a vehicle 61 is provided with a first set of sensors, constituted by two side mounted sensors 62,63 each mounted adjacent to the "A" post of the vehicle. Each sensor 62,63 is an accelerometer, with each accelerometer having a sensing axis 64,65 which makes an angle of 45° longitudinal axis of the vehicle. Each sensing axis is thus directed outwardly and forwardly of the vehicle. The sensing axes are mirror image symmetrical about the longitudinal axis of the vehicle.

25

The vehicle is provided with a second set of sensors constituted by two further sensors 66,67 mounted in the doors of the vehicle or adjacent the "B" post of the vehicle, on opposite sides of the vehicle. The sensors 66,67 in the described embodiment are accelerometers, with each accelerometer having a sensing axis 69 which makes an angle of -45° with the longitudinal axis of the vehicle. Each sensing axis is thus directed outwardly and rearwardly of the vehicle. The sensing axis are mirror image symmetrical about the longitudinal axis of the vehicle.

10

The vehicle is provided with two additional sensors 70,71 mounted in the region of the front bumper 72 of the vehicle. The sensors 70,71 may be contact sensors which respond when the vehicle makes contact with another object or may preferably be accelerometers, in which case the accelerometers may preferably have sensing axes 73,74 which are substantially aligned with the longitudinal axis of the vehicle. However, the sensing axis of the accelerometer 50,51 may be inclined relative to the longitudinal axis of the vehicle, the angle of inclination being between 30° and 60° , positive or negative.

20

All of the sensors are connected to a central control unit 75, which corresponds with the control unit 36 of the embodiment described with reference to Figure 4.

25

In all of the described embodiments the sensors are located close to the outer skin of the vehicle, and thus there are no sensors or accelerometers located in the central part of the vehicle.

Referring now to Figure 7, which is given for purposes of explanation, if the longitudinal axis of the vehicle is the axis X and if a sensor 76, which is provided on the left hand side of the vehicle has a sensing axis 77 which makes an angle of $+45^\circ$ with the longitudinal axis X, then the sensor 76 may measure a
5 positive acceleration $+a$ in a direction which extends forwardly and outwardly of the vehicle and a negative acceleration $-a$ in a direction which extends rearwardly and inwardly of the vehicle.

Similarly, if a second sensor 78 is provided, again mounted on the left
10 hand side of the vehicle, with the sensor having a sensing axis 79 which makes an angle of -45° , then that sensor will sense a positive acceleration in a direction rearwardly and outwardly of the vehicle and a negative acceleration directly inwardly and forwardly of the vehicle.

15 In the present specification "comprises" means "includes or consists of" and "comprising" means "including or consisting of".

The features disclosed in the foregoing description, or the following claims, or the accompanying drawings, expressed in their specific forms or in
20 terms of a means for performing the disclosed function, or a method or process for attaining the disclosed result, as appropriate, may, separately, or in any combination of such features, be utilised for realising the invention in diverse forms thereof.

CLAIMS:

5

1. A crash sensor arrangement in a motor vehicle, the crash sensor arrangement including a first set of sensors comprising respective sensor on each side of the vehicle, each sensor being an accelerometer having a predetermined sensing axis, each sensor being mounted on the vehicle close to
10 the outer skin of the vehicle and at a first longitudinal position such that the sensing axis of each sensor makes a predetermined angle to the longitudinal axis of the vehicle, the predetermined angle being between 30° and 60° , or between -30° and -60° , the sensing axes being mirror symmetrical to each other relative to the longitudinal axis of the vehicle, so that at the said first
15 longitudinal position there are only said two respective sensors, the sensing axes of the two sensors extending in different directions.

20

2. An arrangement according to Claim 1 wherein the predetermined angle is between 40° and 50° , or -40° and -50° .

3. An arrangement according to Claim 1 wherein the predetermined angle is substantially 45° , or -45° .

4. An arrangement according to any one of the preceding Claims wherein
25 the sensing axes of the sensors are directed forwardly and outwardly of the vehicle.

5. An arrangement according to any one Claims 1 to 3 wherein the sensing axes are directed rearwardly and outwardly of the vehicle.

6. An arrangement according to any one of the preceding Claims wherein the sensors are mounted on the vehicle adjacent the "B" posts of the vehicle.

5 7. An arrangement according to any one of Claims 1 to 5 wherein the sensors are mounted on the vehicle adjacent the "C" posts of the vehicle.

8. An arrangement according to any one of the preceding Claims wherein the vehicle is additionally provided with a second set of sensors comprising two
10 further crash sensors, mounted on respective sides of the vehicle at a second longitudinal position spaced from the first longitudinal position.

9. An arrangement according to Claim 8 wherein each further crash sensor of the second set of sensors is a contact sensor.

15

10. An arrangement according to Claim 8 wherein each further crash sensor of the second set of sensors is an accelerometer located close to the outer skin of the vehicle, the sensing axis of the sensors of the second set of sensors being mirror symmetrical to each other relative to the longitudinal axis, but also
20 extending in directions which differ from the directions of the axis of the sensors of the first set of sensors.

11. An arrangement according to Claim 10 wherein the accelerometer of each sensor of the second set of sensors has a sensing axis which extends
25 substantially perpendicularly to the longitudinal axis of the vehicle.

12. An arrangement according to any one Claims 8 to 11 wherein each sensor of the second set of sensors is mounted on the vehicle adjacent an "A" post of the vehicle.

13. An arrangement according to any one Claims 8 to 11 wherein each sensor of the second set of sensors is mounted in a door of the vehicle.

5 14. An arrangement according to any one of the preceding Claims wherein the vehicle is provided with at least one front sensor.

15. An arrangement according to any one of the preceding Claims wherein the vehicle is provided with two front sensors.

10

16. An arrangement according to Claims 14 or Claim 15 wherein the or each front sensor is a contact sensor.

15 17. An arrangement according to Claim 14 or Claim 15 wherein the or each front sensor is an accelerometer.

18. An arrangement according to Claim 17 wherein the sensing axis of each accelerometer forming a front sensor is substantially aligned with the longitudinal axis of the vehicle.

20

19. An arrangement according to Claim 17 wherein the sensing axis of each accelerometer forming a front sensor is between 30° and 60° , or between -30° and -60° relative to the longitudinal axis of the vehicle, the axis of the front sensors being mirror symmetric relative to the longitudinal axis.

25

20. An arrangement according to any one of the preceding Claims wherein a central control unit is provided to receive signals from the sensors and to control the deployment or actuation of one or more safety devices within the vehicle.

21. An arrangement according to any one of the preceding Claims wherein all of the sensors are located close to the outer skin of the vehicle.
- 5 22. A crash sensor arrangement substantially as herein described with reference to and as shown in Figure 1 of the accompanying drawings.
23. A crash sensor arrangement substantially as herein described with reference to and as shown in Figure 2 of the accompanying drawings.
- 10 24. A crash sensor arrangement substantially as herein described with reference to and as shown in Figure 3 of the accompanying drawings.
- 15 25. A crash sensor arrangement substantially as herein described with reference to and as shown in Figure 4 of the accompanying drawings.
26. A crash sensor arrangement substantially as herein described with reference to and as shown in Figure 5 of the accompanying drawings.
- 20 27. A crash sensor arrangement substantially as herein described with reference to and as shown in Figure 6 of the accompanying drawings.
28. Any novel feature or combination of features disclosed herein.

ABSTRACT**“IMPROVEMENTS IN OR RELATING TO A CRASH DETECTION
5 SYSTEM”**

A crash sensor arrangement for a motor vehicle is disclosed. The crash sensor arrangement includes a first set of sensors (3,4) comprising a respective sensor on each side of the vehicle. Each sensor (3,4) is an accelerometer and has a
10 predetermined sensing axis (5,7). Each sensor (3,4) is mounted on the vehicle (1) close to the outer skin of the vehicle and at a first longitudinal position such that the sensing axis (5,7) of each sensor (3,4) makes a predetermined angle to the longitudinal axis (6) of the vehicle (1). The predetermined angle is between
15 30° and 60°, or between -30° and -60°. The sensing axes (5,6) are mirror symmetrical to each other relative to the longitudinal axis (6) of the vehicle (1), so that at said first longitudinal position, there are only said two respective sensors (3,4), the sensing axes of the two sensor extending in different directions.

20

FIGURE 1.

25

FIG 1








FIG 2






FIG 6




FIG 7